

LINIO NEON EOS TV RGBWW

Flexible, cuttable and dimmable tape. Pre-wired tape, simple and quick installation. Easy to mount on smooth surfaces thanks to high quality 3M tape at the back.




One BIN Only to ensure perfect color consistency

Begmever







Minimum Bending Diameter 10mm(0.39")

LINIO NEON EOS TV RGBWW

-To offer millions of colors using red-green-blue-2700K-5500K color mixing. -IP65 protection with high performance silicone, UV resistant, solvents resistant.


-One BIN Only to ensure perfect color consistency. -30m/reel(98.43ft/reel) maximum. And max. run length refers to single side feed in

serial connection. -Easy to be cut and reconnected at project sites. Also, custom length is available as well.

Product Benefits:

-Flexible, cuttable and dimmable LED strip.

-Easy to mount on smooth surfaces thanks to high quality red VHB tape at the back. -Pre-wired LED strip, simple and quick connection.



Electrical data

Voltage	DC24V (23.5V _{min} , 24.5V _{max})
LED PIN Temperature	Max. 65°C /149°F
Storage Temperature	-25°C /-13°F _{min} , 60°C /140°F _{max}
Min. Ambient Tempt.(Ta _{min})	-25°C /-13°F
Max. Ambient Tempt.(Ta _{max})	35°C /95°F@19W
SDCM	3 (2700K)
CRI	Ra90@2700+5500K
Cut Increments	71.4mm/2.81"
Efficacy (lm/W)	51lm/W@RGBWW
Warranty	5 Years


ССТ	Lumen/m	Max. Watt (W/m)	Max. Run Length (m)	
R	59	3	5	
G	171	3	5	
В	33	3	5	
RGB	249	9	5	
2700K	361	5	5	
5500K	358	5	5	
2700K+5500K	722	10	5	
RGBWW2755	968	19	5	

Important notice

-The given data are typical values due to the tolerances of the production process and the electrical components, values for light output and electrical power can vary up to 10%.

-The given color temperature is neon flex (after extrusion) color temperature.

UV-resistant	Waterproof IP65	30m/reel (98.43ft/reel available
		Ð
Solvent- resistant	Life span> 54000H	One Bin Only






Order code

SERIES NAME	COLOR	LENGTH	
LN EOS TV RGBWW	2755=2700K+5500K	05000=5m/196.85"	

Accessories

Art.#	Description	Picture	Art.#	Description	Picture
M0014	Plastic clip		XLG-150- 24-A	PSU 24V/150W IP67, Non- dimmable, White, 100-305V supply	
T0001	VHB 3M adhesive tape		ELG-150- 24B	PSU 24V/150W IP67, 3 in 1 dimming function, White, 100- 305V supply	
Q5+F5- DMX-4A	DC24V, 4A*5 Channel, Max 20A, IP20, support remote control		ELG-150- 24DA	PSU 24V/150W IP67, DALI control technology, White, 100- 305V supply	

Wiring connection




Application



Where to use the product? LINIO NEON EOS TV RGBWW Color Changing Flex Neon Light is a unique and commercial-grade lighting strip. It is ultra-flexible which allows you to achieve the creative design with all the new advanced LED lighting technology. With color-changing flex neon, you can create colorful lighting environments that you probably will not find anywhere else.

Our LINIO NEON EOS TV RGBWW is made with high-quality silicone from Dowcorning. It is flexible, durable, and easy to install. Make your living room more exciting for parties with our RGBWW neon light. You can also turn it into a "happy" place where you can relieve stress after a tiring day.



Example 1: LN EOS TV RGBWW-2755-05000-190: LINIO NEON EOS TV RGBWW, 2700K+5500K, 5m/reel, 19W/m.

Beamever

Address: 100 N Howard St Ste R, Spokane, WA, 99201-0508 USA Tel: 323-5104660 info@beamever.com www.beamever.com