

BELA TAPE RGBW

Flexible,
cuttable and dimmable tape.
Pre-wired tape, simple and
quick installation.
Easy to mount on smooth
surfaces thanks to high quality
3M tape at the back.

One BIN Only to ensure perfect
color consistency






BELA TAPE RGBW

- With 4-in-1 5050 LED(RGB+white),60leds/m and a width of 12mm/0.47".
- Let you to create bolder and more vivid colors than with RGB alone.
- To offer millions of colors by red-green-blue- white color mixing.
- Long lifespan and excellent in heat dissipation.
- One BIN Only to ensure perfect color consistency.
- High CRI90 to present real color.


Product Benefits:

- Flexible, cuttable and dimmable LED strip.
- Easy to mount on smooth surfaces thanks to high quality 3M tape at the back.
- Pre-wired LED strip, simple and quick connection.




Electrical data

Voltage	DC24V (23.5V _{min} 24.5V _{max})
LED PIN Temperature	Max. 65°C /149°F
Storage Temperature	-25°C /-13°F _{min} 60°C /140°F _{max}
SMD Type	5050 (4 in 1)
LEDs/m	60LEDs/m
Efficacy (lm/W)	61lm/W@RGBW40
Max Current/LED	20mA
Cut Increments	100mm/3.94"
Waterproof Rate	IP20
Warranty	5 Years



CCT	Lumen/ft	Max. Watt (W/ft)	Max. Run Length (ft)
R	39	1.46	16.40
G	102	1.46	16.40
B	29	1.46	16.40
W27	167	1.46	16.40
W30	176	1.46	16.40
W35	174	1.46	16.40
W40	189	1.46	16.40
W65	193	1.46	16.40
RGBW40	355	5.85	16.40



Important notice

-The given data are typical values due to the tolerances of the production process and the electrical components, values for light output and electrical power can vary up to 10%.



Order code

SERIES NAME	COLOR	LENGTH	POWER
BELA TAPE RGBW	RGBW27=RGB+2700K	3.94"-1968.50"	585=5.85W
	RGBW30=RGB+3000K		
	RGBW40=RGB+4000K		
	RGBW65=RGB+6500K		


Example 1:
BELA TAPE RGBW27-196.85-585:
BELA TAPE RGBW, W=2700K, 196.85"/
reel, 5.85W/ft.

Example 2:
BELA TAPE RGBW30-196.85-585:
BELA TAPE RGBW, W=3000K, 196.85"/
reel, 5.85W/ft.

Accessories

Art.#	Description	Picture	Art.#	Description	Picture
C0013	Connector for Strip to strip connection, IP20		M4+M4-3A	RF Controller 288W DC24V, 3A*4Channel, Max 12A IP20, Support remote control	
C0014	Connector for Strip to cable connection, IP20		XLG-150-24-A	PSU 24V/150W IP67, Non-dimmable, White, 100-305V supply	
MF008	Male and Female connector, IP20		ELG-150-24B	PSU 24V/150W IP67, 3 in 1 dimming function, White, 100-305V supply	
T0001	VHB 3M adhesive tape		ELG-150-24DA	PSU 24V/150W IP67, DALI control technology, White, 100-305V supply	

Wiring connection




Application



Where to use the product?

BELA TAPE RGBW frees you to unlock various color combinations. Super flexibility and cuttability offers great design freedom, coordinating with DMX controller to achieve lots of vivid lighting effects. 4-in-1 RGBW LEDs from world-famous LED brands, each strip is highly professional and made with precision for you.

Lighting designers can use it for commercial areas such as business offices, luxurious plazas, new products exhibition; or residential areas such as houses, apartments, condos, gardens, etc. Also architectural areas such as pavilion, specific lighting build-up, etc.



Beamever

Address: 100 N Howard St Ste R,
Spokane, WA, 99201-0508 USA
Tel: 323-5104660
info@beamever.com
www.beamever.com