

S

2

2

AERO TAPE IP54

e à

Flexible, cuttable and dimmable tape. Pre-wired tape, simple and quick installation. Easy to mount on smooth surfaces thanks to high quality 3M tape at the back.

One BIN Only to ensure perfect color consistency










AERO TAPE IP54

-With 120 high quality 2835 LEDs per meter and a width of 10mm/0.39". -IP54 protection with top-class silicone, UV resistant, solvents resistant. -Wide color temperature range for your option. -Long lifespan and excellent in heat dissipation. -Use SDCM3 2835 LEDs in One BIN Only to ensure perfect color consistency. -High CRI90 to present real color.

Product Benefits:

-Flexible, cuttable and dimmable LED strip. -Easy to mount on smooth surfaces thanks to high quality 3M tape at the back. -Pre-wired LED strip, simple and quick installation.




Electrical data

Voltage		DC24V (23.5	DC24V (23.5V _{min} , 24.5V _{max})				
LED PIN Temperature		Max. 65°C /149°F					
Storage Temperature		-25°C /-13°F _{min} , 60°C /140°F _{max}					
SMD Type		2835					
LEDs/m		120LEDs/m					
Efficacy (lm/W)		98lm/W@4000K					
SDCM		3 (2700K, 3000K, 4000K)					
CRI		Ra90					
Max Current/LED		50mA@7.32W/ft					
Cut Increments		50mm/1.97'	50mm/1.97"				
Waterproof Rate		IP54					
Warranty		5 Years					
Lumen/ft	1.46W	2.93W	4.39W	5.85 W	7.32W		
2700K	128	269	390	520	668		
3000K	138	277	416	536	705		
3500K	143	287	427	574	717		
4000K	145	291	430	576	722		
6500K	149	295	437	577	719		
Max. Run Length(ft)	16.40	16.40	16.40	16.40	16.40		

Important notice

-The given data are typical values due to the tolerances of the production process and the electrical components, values for light output and electrical power can vary up to 10%.



Life span 54000H

One Bin Onl

F




Order code

Oldel code						
SERIES NAME	COLOR	LENGTH				
AERO TAPE IP54	27= 2700K	1.97"-196.85"				
	30= 3000K					
	35= 3500K					
	40=4000K					
	65=6500K					

Accessories

Art.#	Description	Picture	Art.#	Description	Picture
C0003	Connector for Strip to strip connection, IP20		T0001	VHB 3M adhesive tape	
C0004	Connector for Strip to cable connection, IP20		XLG-150- 24-A	PSU 24V/150W IP67, Non- dimmable, White, 100-305V supply	
MF001	Male and Female connector, IP20		ELG-150- 24B	PSU 24V/150W IP67, 3 in 1 dimming function, White, 100- 305V supply	
MF002	Male and Female DC connector, IP44		ELG-150- 24DA	PSU 24V/150W IP67, DALI control technology, White, 100- 305V supply	

Wiring connection



Application



Where to use the product? AERO TAPE IP54 is called Magic Tape, because it can help accomplish so much incredible work for your lighting projects. For example, by creating stunning lights effectively and elegantly by ONE BIN ONLY, CRI90, and great material quality. Super durable, and trust-worthy for long-term performance.

Applicable for various locations, such as livening up your offices to shine everything in gorgeous lighting day and night, decorating your kitchen to create a warm, cosy, and homely culinary haven.

POWER
146=1.46W
293=2.93W
439=4.39W
585=5.85W
732=7.32W

Example 1: AERO TAPE IP54-27-196.85-146: AERO TAPE IP54, 2700K, 196.85"/reel, 1.46W/ft.

Example 2: AERO TAPE IP54-30-196.85-096: AERO TAPE IP54, 3000K, 196.85"/reel, 2.93W/ft.

Beamever

Address: 100 N Howard St Ste R, Spokane, WA, 99201-0508 USA Tel: 323-5104660 info@beamever.com www.beamever.com

+ DC24V