

ARCUS VALUE 3D LARGE

Indoor · Dual Bending · Static White

Features

- Uniform and stable illumination with delicate, natural light quality.
- IP54 rated, ideal for indoor uses
- 5 years warranty

Applications


Living rooms, TV walls, feature walls, under-cabinet areas, staircases, ceiling coves, hallways, etc.

Date _____ Fixture type _____

Project name _____ Project phase _____



Dimensions



Order Code

Model	Environment	Voltage	CCT	Power	End Cap	Left Feed Entry
AV3DL	D4-Dry (IP54)	24-DC24V	22-2200K 27-2700K 30-3000K 35-3500K 40-4000K	100-10W/M	IJ Injected (IP54) IJC Clear injected (IP54) SEC Silicone (IP54)	F Front OW Open wire 30cm B Bottom MC Male connector with 30cm cable S Side FC Female connector with 30cm cable C Closed NA Only for Closed Feed Entry

*Injected and clear injected end cap are factory-made only.

Assembly Builder

Assembly Builder

Right Feed Entry			Length	
F	Front	OW	Open wire 30cm	Max. nominal 5m
B	Bottom	MC	Male connector with 30cm cable	Increment 62.5mm
S	Side	FC	Female connector with 30cm cable	
C	Closed	NA	Only for Closed Feed Entry	

*We will manufacture to the requested length considering the increment length.

Mounting Order Code

Product Code

Please select on the Mounting Options page.

Lumen Output (lm/m)

Temp./Color	10W/M
2200K	710
2700K	810
3000K	830
3500K	850
4000K	850
Max. Run Length(M)	5
Storage Temperature	-40°C~ 60°C
Operating Temperature	-40°C~ 45°C

Technical Details


Efficacy	85lm/W @4000K 10W
CRI	Ra≥90
Beam Angle	110°
LED MacAdam	5 steps
Average Life (L70)	> 44,000 hours
Max. Length Per Reel	10M

ARCUS VALUE 3D LARGE


Indoor · Dual Bending · Static White

Feed Entry / End Cap Options


IJ: Injected end cap – IP54, factory-made only



IJC: Clear injected end cap – IP54, factory-made only




SEC: Silicone end cap – IP54



Connector Wire Options



OW: Open wire, **Dry only**
Standard 1m (3.28ft), 18 AWG (wire length customizable)



MC: Male connector, **Wet**
Standard 30cm (0.98ft), 18 AWG





FC: Female connector, **Wet**
Standard 30cm (0.98ft), 18 AWG



ARCUS VALUE 3D LARGE

Indoor · Dual Bending · Static White



Mounting Options

**ARCUS-L-SC**



Name	Straight surface channel
Material	Aluminum
Standard Length	1M (3.28ft)

**ARCUS-L-BC**


Name	Bendable surface channel
Material	Aluminum
Standard Length	1M (3.28ft)

**ARCUS-L-RC**



Name	Straight recessed channel
Material	Aluminum
Standard Length	1M (3.28ft)

**ARCUS-L-MC**



Name	Mud-in channel
Material	Aluminum
Standard Length	1M (3.28ft)

**ARCUS-L-BMC**



Name	Bendable mud-in channel
Material	Aluminum
Standard Length	1M (3.28ft)

**ARCUS-L-SCS**


Name	Straight surface channel with silicone groove
Material	Aluminum
Standard Length	1M (3.28ft)

**ARCUS-L-LBC**

Name	Light-block channel
Material	Aluminum
Standard Length	1M (3.28ft)

**ARCUS-L-PC**





Name	PC channel
Material	Polycarbonate
Standard Length	1M (3.28ft)

**ARCUS-L-CL**

Name	Mounting clip
Material	Aluminum
Standard Length	25mm (0.98in.)

ARCUS VALUE 3D LARGE

Indoor · Dual Bending · Static White

			ARCUS-L-LS Name L-shaped mounting bracket Material Aluminum Standard Length 20mm(0.79in.) * ARCUS-L-LS can be installed with aluminum channel ARCUS-L-SC.
			ARCUS-L-AC Name Adjustable mounting clip Material Stainless steel Standard Length 25.5mm (1 in.) * ARCUS-L-LS can be installed with aluminum channel ARCUS-L-SC.
			ARCUS-L-RC-SPC Name Spring clip Standard Pkg 1pcs * ARCUS-L-RC-SPC must be installed with aluminum channel ARCUS-L-RC.

End Caps (Optional, purchase for extra)

			
ARCUS-L-SEC-C Silicone closed end cap	ARCUS-L-SEC-F-2P Silicone end cap front entry with 30cm (0.98ft) cable, 2 pin	ARCUS-L-SEC-S-2P Silicone end cap side entry with 30cm (0.98ft) cable, 2 pin	ARCUS-L-SEC-B-2P Silicone end cap bottom entry with 30cm (0.98ft) cable, 2 pin

Additional Accessories (Optional, purchase for extra)

			
MCW-2P-67 Male connector with 30cm (0.98ft) white cable, 2 pin, IP67, Wet, 18 AWG	FCW-2P-67 Female connector with 30cm (0.98ft) white cable, 2 pin, IP67, Wet, 18 AWG	MCB-2P-67 Male connector with 30cm (0.98ft) black cable, 2 pin, IP67, Wet, 18 AWG	FCB-2P-67 Female connector with 30cm (0.98ft) black cable, 2 pin, IP67, Wet, 18 AWG

ARCUS VALUE 3D LARGE

Indoor · Dual Bending · Static White

Drivers

Non-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
XLG-150-24-A	150W	100-305VAC	24V	Dry/Damp/IP67	180 * 63 * 35.5 mm
LPV-150-24	150W	100-277VAC		Dry/Damp/IP67	148 * 40 * 30 mm
LRS-150-24	150W	85-132VAC / 170-264VAC		Dry	99 * 97 * 30 mm

3 in 1-dimmable


Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24B-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm
PWM-120-24	120W	90-305VAC / 127-431VAC		Dry/Damp/IP67	191 * 63 * 37.5 mm

DALI control technology


Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24DA-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm

Wiring Diagram


Non-dimmable



3 in 1-dimmable



DALI Control Technology



ARCUS VALUE 3D LARGE

Indoor · Dual Bending · Static White

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG
5W / 0.2A	527.3 m	238.9 m	121.0 m	80.2 m	53.3 m	39.9 m	32.6 m
10W / 0.4A	263.6 m	119.4 m	60.7 m	40.2 m	26.8 m	20.1 m	16.5 m
15W / 0.6A	175.9 m	79.6 m	40.2 m	26.8 m	17.7 m	13.4 m	11.0 m
20W / 0.8A	132.0 m	59.7 m	30.2 m	20.1 m	13.4 m	10.1 m	8.2 m
25W / 1.0A	105.5 m	47.9 m	24.1 m	16.2 m	10.7 m	7.9 m	6.7 m
30W / 1.3A	88.1 m	39.9 m	20.1 m	13.4 m	8.8 m	6.7 m	5.5 m
35W / 1.5A	75.6 m	34.1 m	17.4 m	11.6 m	7.6 m	5.8 m	4.6 m
40W / 1.7A	66.1 m	29.9 m	15.2 m	10.1 m	6.7 m	4.9 m	4.0 m
45W / 1.9A	58.5 m	26.5 m	13.4 m	8.8 m	5.8 m	4.3 m	3.7 m
50W / 2.1A	52.7 m	23.8 m	12.2 m	7.9 m	5.5 m	4.0 m	3.4 m
55W / 2.3A	47.9 m	21.6 m	11.0 m	7.3 m	4.9 m	3.7 m	3.0 m
60W / 2.5A	43.9 m	19.8 m	10.1 m	6.7 m	4.6 m	3.4 m	2.7 m
65W / 2.7A	40.5 m	18.3 m	9.1 m	6.1 m	4.3 m	3.0 m	2.4 m
70W / 2.9A	37.8 m	17.1 m	8.5 m	5.8 m	4.0 m	3.0 m	2.4 m
75W / 3.1A	35.4 m	15.9 m	7.9 m	5.2 m	3.7 m	2.7 m	2.1 m
80W / 3.3A	33.2 m	14.9 m	7.6 m	4.9 m	3.4 m	2.4 m	2.1 m
85W / 3.5A	31.4 m	14.0 m	7.0 m	4.6 m	3.0 m	2.4 m	1.8 m
90W / 3.8A	29.6 m	13.4 m	6.7 m	4.6 m	3.0 m	2.1 m	1.8 m
96W / 4.0A	27.7 m	12.5 m	6.4 m	4.3 m	2.7 m	2.1 m	1.8 m