

LINIO NEON 1617 SV HE

Outdoor · Horizontal Bending · Static White

Features

- Robust & uniform silicone body, with high lumen output up to 81.5 lm/W
- IP67 rated, ideal for outdoor uses
- 5 years warranty


Applications

Hotels, apartment, lobby hall, shopping mall, facades, gardens, parks, balconies, roofs, soffits, etc.




Date _____ Fixture type _____

Project name _____ Project phase _____



Dimensions



Order Code

Model	Environment	Voltage	CCT	Power	End Cap	Left Feed Entry
LN1617SVHE	W7-Wet (IP67)	24-DC24V	22-2200K 27-2700K 32-3200K 35-3500K 40-4000K 57-5700K	096-9.6W/M 150-15W/M	IJ Injected (IP67) IJC Clear injected (IP67) SEC Silicone (IP67) MEC Mechanical with screws (IP67)	F Front OW Open wire 30cm B Bottom MC Male connector with 30cm cable S Side FC Female connector with 30cm cable C Closed NA Only for Closed Feed Entry J Jumper

*Injected and clear injected end cap are factory-made only. *Jumper feed entry must be used in conjunction for wire-in and wire-out directions.

Assembly Builder

Right Feed Entry	Length
F Front OW Open wire 30cm B Bottom MC Male connector with 30cm cable S Side FC Female connector with 30cm cable C Closed NA Only for Closed Feed Entry J Jumper	Max. nominal 10m Increment 62.5mm

*Jumper feed entry must be used in conjunction for wire-in and wire-out directions. *We will manufacture to the requested length considering the increment length.

Mounting Order Code

Product Code
Please select on the Mounting Options page.

Lumen Output (lm/m)

Temp./Color	9.6W/M	15W/M
2200K	610	937
2700K	685	1048
3200K	748	1155
3500K	758	1157
4000K	785	1172
5700K	747	1137
Max. Run Length (m)	10	5
Storage Temperature	-40°C- 60°C	
Operating Temperature	-40°C- 45°C	

Technical Details


Efficacy	81.5lm/W @4000K 9.6W
CRI	Ra≥90
Beam Angle	110°
LED MacAdam	2 steps
Average Life (L70)	> 54,000 hours
Max. Length Per Reel	20M
Finish	Matte

LINIO NEON 1617 SV HE

Outdoor · Horizontal Bending · Static White

Photometry

LN1617SVHE-W7-24-35-096-IJ-F-OW-F-OW
LINIO NEON 1617 SV HE, Horizontal bend, 3500K, 9.6W/M



AVERAGE BEAM ANGLE(50%):111.3 DEG

Zonal Lumen Summary 3500K

Zone	Lumen	% Fixture
0-30	61.63	27%
0-40	100.8	44.1%
0-60	177.6	77.8%
0-90	225.7	98.9%
0-180	228.3	100%

UNIT: CD

— C0/180, 110.8


— C30/210, 111.1

— C60/240, 111.5


— C90/270, 111.8

Feed Entry / End Cap Options


IJ: Injected end cap – IP67, factory-made only




IJC: Clear injected end cap – IP67, factory-made only



SEC: Silicone end cap – IP67



MEC: Mechanical end cap with screws – IP67



LINIO NEON 1617 SV HE

Outdoor · Horizontal Bending · Static White

Connector Wire Options



OW: Open wire, **Dry only**
Standard 30cm (0.98ft), 18 AWG (wire length customizable)





MC: Male connector, **Wet**
Standard 30cm (0.98ft), 18 AWG





FC: Female connector, **Wet**
Standard 30cm (0.98ft), 18 AWG

Mounting Options






LN1617-SC

Name	Straight surface channel
Material	Aluminum
Standard Length	1M (3.28ft)





LN1617-BC

Name	Bendable surface channel
Material	Aluminum
Standard Length	1M (3.28ft)





LN1617-RC

Name	Straight recessed channel
Material	Aluminum
Standard Length	1M (3.28ft)





LN1617-MC

Name	Mud-in channel
Material	Aluminum
Standard Length	1M (3.28ft)





LN1617-BMC

Name	Bendable mud-in channel
Material	Aluminum
Standard Length	1M (3.28ft)





LN1617-SCS

Name	Straight surface channel with silicone groove
Material	Aluminum
Standard Length	1M (3.28ft)



LN1617-LBC

Name	Light-block channel
Material	Aluminum
Standard Length	1M (3.28ft)




LN1617-PC

Name	PC channel
Material	Polycarbonate
Standard Length	1M (3.28ft)


LINIO NEON 1617 SV HE

Outdoor · Horizontal Bending · Static White



LNI617-CL


Name	Mounting clip
Material	Aluminum
Standard Length	25mm (0.98in.)



LNI617-LS

Name	L-shaped mounting bracket
Material	Aluminum
Standard Length	20mm(0.79in.)



* LNI617-LS can be installed with aluminum channel LNI617-SC.



LNI617-AC

Name	Adjustable mounting clip
Material	Stainless steel
Standard Length	25.5mm (1 in.)

* LNI617-LS can be installed with aluminum channel LNI617-SC.



LNI617-RC-SPC

Name	Spring clip
Standard Pkg	1pcs

* LNI617-RC-SPC must be installed with aluminum channel LNI617-RC.

End Caps (Optional, purchase for extra)



LNI617-SEC-C
Silicone closed end cap



LNI617-SEC-F-2P
Silicone end cap front entry with 30cm (0.98ft) cable, 2 pin



LNI617-SEC-S-2P
Silicone end cap side entry with 30cm (0.98ft) cable, 2 pin



LNI617-SEC-B-2P
Silicone end cap bottom entry with 30cm (0.98ft) cable, 2 pin



LNI617-MEC-C
Mechanical closed end cap with screws



LNI617-MEC-F-2P
Mechanical end cap with screws, front entry with 30cm (0.98ft) cable, 2 pin



LNI617-MEC-LS-2P
Mechanical end cap with screws, left side entry with 30cm (0.98ft) cable, 2 pin



LNI617-MEC-RS-2P
Mechanical end cap with screws, right side entry with 30cm (0.98ft) cable, 2 pin



LNI617-MEC-B-2P
Mechanical end cap with screws, bottom entry with 30cm (0.98ft) cable, 2 pin



LNI617-JC-F-2P
Jumper connector front entry with 7cm (0.23ft) cable, 2 pin, IP67

Additional Accessories (Optional, purchase for extra)



MCW-2P-67
Male connector with 30cm (0.98ft) white cable, 2 pin, IP67, Wet, 20 AWG



FCW-2P-67
Female connector with 30cm (0.98ft) white cable, 2 pin, IP67, Wet, 20 AWG



MCB-2P-67
Male connector with 30cm (0.98ft) black cable, 2 pin, IP67, Wet, 20 AWG



FCB-2P-67
Female connector with 30cm (0.98ft) black cable, 2 pin, IP67, Wet, 20 AWG

LINIO NEON 1617 SV HE

Outdoor · Horizontal Bending · Static White

Drivers

Non-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
XLG-150-24-A	150W	100-305VAC	24V	Dry/Damp/IP67	180 * 63 * 35.5 mm
LPV-150-24	150W	100-277VAC		Dry/Damp/IP67	148 * 40 * 30 mm
LRS-150-24	150W	85-132VAC / 170-264VAC		Dry	99 * 97 * 30 mm


3 in 1-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24B-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm
PWM-120-24	120W	90-305VAC / 127-431VAC		Dry/Damp/IP67	191 * 63 * 37.5 mm

DALI control technology

Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24DA-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm

Wiring Diagram



LINIO NEON 1617 SV HE

Outdoor · Horizontal Bending · Static White

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG
5W / 0.2A	527.3 m	238.9 m	121.0 m	80.2 m	53.3 m	39.9 m	32.6 m
10W / 0.4A	263.6 m	119.4 m	60.7 m	40.2 m	26.8 m	20.1 m	16.5 m
15W / 0.6A	175.9 m	79.6 m	40.2 m	26.8 m	17.7 m	13.4 m	11.0 m
20W / 0.8A	132.0 m	59.7 m	30.2 m	20.1 m	13.4 m	10.1 m	8.2 m
25W / 1.0A	105.5 m	47.9 m	24.1 m	16.2 m	10.7 m	7.9 m	6.7 m
30W / 1.3A	88.1 m	39.9 m	20.1 m	13.4 m	8.8 m	6.7 m	5.5 m
35W / 1.5A	75.6 m	34.1 m	17.4 m	11.6 m	7.6 m	5.8 m	4.6 m
40W / 1.7A	66.1 m	29.9 m	15.2 m	10.1 m	6.7 m	4.9 m	4.0 m
45W / 1.9A	58.5 m	26.5 m	13.4 m	8.8 m	5.8 m	4.3 m	3.7 m
50W / 2.1A	52.7 m	23.8 m	12.2 m	7.9 m	5.5 m	4.0 m	3.4 m
55W / 2.3A	47.9 m	21.6 m	11.0 m	7.3 m	4.9 m	3.7 m	3.0 m
60W / 2.5A	43.9 m	19.8 m	10.1 m	6.7 m	4.6 m	3.4 m	2.7 m
65W / 2.7A	40.5 m	18.3 m	9.1 m	6.1 m	4.3 m	3.0 m	2.4 m
70W / 2.9A	37.8 m	17.1 m	8.5 m	5.8 m	4.0 m	3.0 m	2.4 m
75W / 3.1A	35.4 m	15.9 m	7.9 m	5.2 m	3.7 m	2.7 m	2.1 m
80W / 3.3A	33.2 m	14.9 m	7.6 m	4.9 m	3.4 m	2.4 m	2.1 m
85W / 3.5A	31.4 m	14.0 m	7.0 m	4.6 m	3.0 m	2.4 m	1.8 m
90W / 3.8A	29.6 m	13.4 m	6.7 m	4.6 m	3.0 m	2.1 m	1.8 m
96W / 4.0A	27.7 m	12.5 m	6.4 m	4.3 m	2.7 m	2.1 m	1.8 m